Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L2	2316	375/343	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L3	197	(coarse adj frequency) and correlat\$3 and accumulat\$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L4	263	(frequency adj offset) with (component or quadrature or QAM) with filter\$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L5	35	375/310	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L6	2033	375/344	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L7	454	(dc or frequency) adj (offset) with (filter or filtering) and (WLAN or "802. 11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L8	0	"10/700474"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

		·				
L9	2033	375/344	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L10	67	(fir or (finite adj impulse adj response)) with correlat\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L11	1577	(frequency adj offset) with (component or quadrature or QAM)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L12	263	(frequency adj offset) with (component or quadrature or QAM) with filter\$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L13	2	"6930989".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L14	67	(fir or (finite adj impulse adj response)) with correlat\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L15	0	"10/700474"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

L16	. 0	"10700474"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2007/09/18 11:26
			DERWENT; IBM_TDB			•
L17	454	(dc or frequency) adj (offset or synchonization) with (filter or filtering) and (WLAN or "802.11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L18	. 0	(coarse adj frequency) same correlati\$2 same accumulati\$2 same (short adj preamble) same window	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L19	0	(coarse adj frequency) with autocorrelati\$2 with accumulati\$2 with (short adj preamble) with window	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L20	1577	(frequency adj offset) with (component or quadrature or QAM)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR .	ON	2007/09/18 11:26
L21	448	375/319	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L22	2	"6930989".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

			Γ	T	·	<u> </u>
L23	454	(dc or frequency) adj (offset) with (filter or filtering) and (WLAN or "802. 11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L24	83	(dc or frequency) adj (offset) with (filter or filtering) same (WLAN or "802.11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L25	83	(dc or frequency) adj (offset) with (filter or filtering) same (WLAN or "802.11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L26	81	(dc or frequency) adj (offset or synchonization) with (WLAN or "802. 11")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L27	0	(coarse adj frequency) same correlati\$2 same accumulati\$2 same (short adj preamble)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L28	0	coarse adj frequency adj estimation with autocorrelati\$2 withaccumulati\$2 with (short adj preamble) with window	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L29	33	(dc or frequency) adj (offset) with (filter or filtering) with (WLAN or "802. 11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:41

L30	2	"20040196915".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L31	0	"10768073"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L32	448	375/319	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L33	0	"10/768073"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L34	86	(coarse adj frequency) and correlati\$2 and accumulati\$2	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L35	0	"10700474"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L36 ·	0	(coarse adj frequency) same autocorrelati\$2 same accumulati\$2 same (short adj preamble) same window	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

L37	81	(dc or frequency) adj (offset or synchonization) with (WLAN or "802. 11")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L38	454	(dc or frequency) adj (offset or synchonization) with (filter or filtering) and (WLAN or "802.11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L39		"09/352404"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L40	95	(frequency adj offset) with (quadrature or QAM) with filter\$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L41	0	L40 and L21	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L42	51	((fir or (finite adj impulse adj response)) with filter\$3 ) with correlat\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L43		L40 and L5	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

L44	1	(coarse adj frequency) same correlati\$2 same accumulati\$2	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L45	1	(frequency adj offset) with (quadrature or QAM) with filter\$3 and WLAN	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L46		"10/396118"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L47	1	"09/352404"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L48	1	"10/396118"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L49	12	L3 and L2	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L50	33	(dc or frequency) adj (offset) with (filter or filtering) with (WLAN or "802. 11" or OFDM or hyperlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

		1. 2. 3. 1.		T 05		2007/20/40 44 55
L51	54	(frequency adj offset) and (quadrature or QAM) and (FIR with filter\$3) and WLAN	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L52		(frequency adj offset) and (quadrature or QAM) and (FIR with filter\$3) and WLAN and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L53	6	moose.in. and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L54	4	L3 and L32	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L55	2	"2004196915".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L56	43	((fir or (finite adj impulse adj response)) with filter\$3 ) with correlat\$3 and ("802.11" or wlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L57	20	(frequency adj offset) with (component or quadrature or QAM) with filter\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

L58	20	(frequency adj offset) with (component or quadrature or QAM) with filter\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L59	2	"20040005018".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L60	2	(frequency adj offset) with (quadrature or QAM) with filter\$3 with averag\$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L61	51	((fir or (finite adj impulse adj response)) with filter\$3 ) with correlat\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L62	15	L3 and L6	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L63	2	"7039000".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L64	43	((fir or (finite adj impulse adj response)) with filter\$3 ) with correlat\$3 and ("802.11" or wlan)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

L65	6	moose.in. and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON .	2007/09/18 11:26
L66	2	"6,633,616".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L67	188	averag\$3 with normaliz\$3 and ofdm	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L68	6	(DC adj offset) WITH OFDM and qam and "802.11a"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L69	12	(DC adj offset) WITH OFDM and qam	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L70	216	accumulator with (FIR adj filter)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L71	5	(low adj complexity) same (FIR adj filter) and OFDM	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

						•
L72	1	(low adj complexity) with (FIR adj filter) and OFDM	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L73	62	(DC adj offset) WITH OFDM	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L74	25	"929027"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L75	63	(DC adj offset) and OFDM and qam and "802.11a"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L76	24	accumulator same (FIR adj filter) and OFDM	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON .	2007/09/18 11:26
L77	2	"20050111525".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L78	3	accumulator with (FIR adj filter) and OFDM	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26

L79	4	averag\$3 with normaliz\$3 and ofdm and (dc adj offset)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L80	10	(low adj complexity) with (FIR adj filter)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:26
L81	21	accumulator near (FIR adj filter)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR .	ON	2007/09/18 11:29
L82	2	"7155185".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:29
L83	2	"20050025041".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:34
L84	2	"20060203926".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR .	ON	2007/09/18 11:36
L85	2	"20030152021".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR .	ON	2007/09/18 11:37

L86		"20030058975".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:38
L87	2	"20030058966".pn.	US-PGPÚB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:38
L88	17	(dc adj offset) same (filter or filtering) same subcarrier	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:45
L90	3	((dc adj offset) same (filter or filtering) same subcarrier).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:45
L91	5	((dc adj offset) and (filter or filtering) and subcarrier).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:47
L92	2	((dc adj offset) and (filter or filtering) and subcarrier and preamble).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/09/18 11:46

Web Images Video News Maps Gmail more ▼ drjatorres@gmail.com | My Notebooks | Web History | My Account | Sign out Google Advanced Search "DC offset" ofdm "802.11a" "subcarrier compo Search Preferences Results 1 - 10 of about 841 for "DC offset" ofdm "802.11a". (0.35 seconds) Web

[PDF] DC offset estimation in OFDM based WLAN application - Global ... Abstract - The effect of a DC offset on the OFDM Wireless LAN ... offset added to the

Wireless LAN 802.11a or 802.11.g signal ...

ieeexplore.ieee.org/iel5/9481/30082/01379023.pdf - Similar pages - Note this

[PDF] A single-chip transceiver for 802.11a and hiperlan2 wireless LANs ... as they are both based on OFDM (orthogonal frequency, division multiplexing) modulation and .... In order to reduce the DC offset produced by the direct ... ieeexplore ieee org/iel5/8611/27289/01213887.pdf - Similar pages - Note this [ More results from ieeexplore.ieee.org ]

CommsDesign - Compensation for Mixed-Signal Errors in 802.11a ZIF ... Thus, ZIF architectures must provide gain adjustment and DC offset correction capabilities to be successful in an 802.11a design. ... www.commsdesign.com/design\_corner/showArticle.jhtml?articleID=16505842 - 48k -Cached - Similar pages - Note this

CommsDesign - RF Simulation Improves 802.11a System Performance Per the 802.11a OFDM modulation scheme, the framed WLAN signal is routed through a power amplifier and sent to a receiver. ... www.commsdesign.com/story/OEG20020218S0034 - 50k -Cached - Similar pages - Note this [ More results from www.commsdesign.com ]

DC offset estimation and compensation in OFDM radio receivers by ... DC offset estimation and compensation in OFDM radio receivers by weighted averaging over a ..... 1 shows a burst structure based on IEEE Standard 802.11a/g; ... www.freepatentsonline.com/20050025041.html - 63k - Cached - Similar pages - Note this

Apparatus and method for detecting preambles according to IEEE ... The first sub-unit is devoted to detecting 802.11a preambles while the second sub-unit tackles 802.11b preambles. DC offset free baseband I/Q signals are ... www.freepatentsonline.com/20060199558.html - 31k - Cached - Similar pages - Note this [ More results from www.freepatentsonline.com ]

Apparatus and methods for eliminating DC offset in a wireless ... The present invention relates to direct current (DC) offset cancellation, ... IEEE 802.11a standard, uses orthogonal frequency division multiplexing (OFDM). ... www.patentstorm.us/patents/7155185-description.html - 35k -Cached - Similar pages - Note this

Flexible Chip Set Arms 802.11a/b/g WLANs The RF5421 baseband/MAC IC includes a complete implementation of IEEE 802.11a/b/g CCK and OFDM modems and an ARM9 processor that executes the bulk of the ... www.mwrf.com/Articles/ArticleID/5427/5427.html - Similar pages - Note this

[PDF] WB60014a-IEEE802.11a/g DigitalbasebandModem

File Format: PDF/Adobe Acrobat - View as HTML

IEEE 802.11 a/g OFDM standard. In addition, correction. algorithms for compensation of ... Tx\_DC\_acc. Tx DC-offset accuracy. <1 LSB <2LSB. bits. 802.11a/g. www.wavebreaker.se/WB60014a%20WLAN%20Modem.pdf - Similar pages - Note this

[PDF] Flexible Chip Set Arms 802.11a/b/gWLANs

File Format: PDF/Adobe Acrobat - View as HTML A DC offset loop, operates in conjunction with the base-, band to dynamically correct for ... An 802.11a/g OFDM modem. 3. An 802.11b CCK modem. cover story ... www.rfmd.com/pdfs/Flexible%20Chip%20Set%20Arms.pdf - Similar pages - Note this

> 1 2 3 4 5 6 7 8 9 10 <u>Next</u>

Try Google Desktop: search your computer as easily as you search the web.

"DC offset" ofdm "802.11a"

Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google

 Web Images
 Video
 News
 Maps
 Gmail
 more ▼

 drjatorres@gmail.com | My Notebooks | Web History | My Account | Sign out

 Google

 "DC offset" ofdm "802.11a" "subcarrier compo
 Search Preferences

 Web
 Results 1 - 1 of 1 for "DC offset" ofdm "802.11a" "subcarrier components". (0.32 seconds)

 Tip: Try removing quotes from your search to get more results.

Systems Using Alternating Or Pulsating Current - Plural Channels ...

A method and system for estimating **DC offset** and removing the excess **DC offset** from samples used by an overlap-and-add operation at the receiver of **OFDM** ...

www.freshpatents.com/x1375260000psbc.php - 370k - Cached - Similar pages - Note this

Download Google Pack: free essential software for your PC

"DC offset" ofdm "802.11a" "subcarr Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google

News Maps Gmail more + Images Video

drjatorres@gmail.com | My Notebooks | Web History | My Account | Sign out

Google

"DC offset" ofdm "802.11a" filtering

Search

Advanced Search Preferences

Web

Results 1 - 10 of about 718 for "DC offset" ofdm "802.11a" filtering. (0.35 seconds)

AC/DC Filters by Radius

Comprehensive line of Std & Sponsored Link www.radiuspower.com AC/DC, Single & 3 Phase EMI Filters

### Apparatus and methods for eliminating DC offset in a wireless ...

A wireless receiver operating, for example, in accordance with the IEEE 802.11a standard, uses orthogonal frequency division multiplexing (OFDM). ...

www.freepatentsonline.com/7155185.html - 48k -Cached - Similar pages - Note this

#### DC offset estimation and compensation in OFDM radio receivers by ...

The DC offset is once again at the frequency zero, but the filter no longer has a zero ..... 1 shows a burst structure based on IEEE Standard 802.11a/g; ... www.freepatentsonline.com/20050025041.html - 63k -

Cached - Similar pages - Note this [ More results from www.freepatentsonline.com ]

### [PDF] DC offset estimation in OFDM based WLAN application - Global ...

around each OFDM sub-carrier, as described above. The DC offset is generated at the receiver input and therefore. remains at frequency zero, but each filter ...

ieeexplore.ieee.org/iel5/9481/30082/01379023.pdf -Similar pages - Note this

### [PDF] An effective scheme to improve performance of **OFDM**-based system ...

filter. -b. kirmticn. Q. -\*. 4. 4-IF based scheme for DC offset cancellation .... IEEE 802.11a while for other standards like ... ieeexplore.ieee.org/iel5/8586/27227/01209743.pdf -Similar pages - Note this

[ More results from ieeexplore.ieee.org ]

## CommsDesign - Compensation for Mixed-Signal Errors in 802.11a ZIF ...

Thus, ZIF architectures must provide gain adjustment and DC offset correction capabilities to be successful in an 802.11a design. ...

www.commsdesign.com/design\_corner/showArticle.jhtml?articleID=16505842 - 48k -Cached - Similar pages - Note this

## A Fully-integrated 2.4/5.7 GHz Concurrent Dual-band 0.18 µm CMOS ...

A 2.4/5.7 GHz dual-band WLAN system, which supports both 802.11a and 802.11b/g, ... the DC offset can be removed by a high pass filter with a corner ...

Sponsored Links

#### Instant EMI Filter

Slip a high-performance EMI filter into your connector in seconds. www.EESeal.com

#### Sprint Mobile Broadband Explore Variety of Phones, Mobile

Broadband Cards, All-In-One Devices Sprint.com/business

## **Great Printing Specials**

Buy 500 and Get 500 FREE! Super Low Prices, Great Quality www.moderncolorprinting.com

#### 48 Hour Print

Quick, quality printing services! Order from 48hourprint and save! www.48hourprint.com

#### Print 5000 biz cards \$99

full color, 2 sides 12 pt uv coated flyers, brochures, letterheads www.24hsprinting.com

#### filters Huge Selection

**Huge filters Selection** Free UPS, 20-70% Off, Low Prices! www.OpticsPlanet.net

#### American Air **Filter**

Buy your filters online Free shipping on furnace filters www.americanairfilter.com

www.mwjournal.com/article.asp?HH\_ID=AR\_1308 - 45k - Cached - Similar pages - Note this

[PDF] Chapter 4 SYSTEM DESIGN OF A SIP RECEIVER FOR IEEE 802.11A/B/G WLAN channel, dc offset and 1/f noise can be uncomplicatedly removed by a ..... Gain and filter-order plan for 802.11a/g in OFDM mode at the (a) lowest and ... www.springerlink.com/index/x1g2721x34276k76.pdf - Similar pages - Note this

Method and system for tracking and mitigating DC offset in the ...

Timing and frequency synchronization of OFDM signals Issued on: March 24, ... 2, the DC offset estimated from averaging or notch-filtering is not perfect, ...

www.patentstorm.us/patents/7035589-description.html - 28k Cached - Similar pages - Note this

MAX2830 - NEW! - 2.4GHz to 2.5GHz 802.11g/b RF Transceiver with PA ... The MAX2830 completely eliminates the need for an external SAW filter by ... These devices are suitable for the full range of 802.11g OFDM data rates (6Mbps ... www.maxim-ic.com/quick\_view2.cfm/qv\_pk/5367 - 27k - Cached - Similar pages - Note this

An Innovative RF CMOS IP Using a 10 GHz VCO for Direct Conversion WLAN Our solution is compliant with the 802.11a/b/g standards. ... Therefore the DC offset system bandwidth, in the case of OFDM signals, has for upper bound the ... www.us.design-reuse.com/articles/article7900.html - 49k - Cached - Similar pages - Note this

1 2 3 4 5 6 7 8 9 10 Next

Try Google Desktop: search your computer as easily as you search the web.

"DC offset" ofdm "802.11a" filtering Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google



About Us

scirus -	<b>▼</b> Searc	ch) +   ØPop-up Bl	ocker OFF 🏻 🥒 Highlight
lvisory Board	Submit Web Site	Help	Contact Us

**Basic Search** 

Newsroom

Advanced Search Preferences

٠		"DC offset" AND ofdm AND "802.11a" AND filtering AN Search	
		☑ Journal sources ☑ Preferred Web sources ☑ Other Web sources ☐ Exact phrase	
	Se	earched for:: :All of the words:"DC offset" AND ofdm AND "802.11a" AND filtering AND subcarrie	r
		Found:: :7 total   0 journal results   7 preferred web results   0 other web results	
		Sort by:: :relevance   date	
		Save checked results Email checked results Export checked results	Dic
	1.	Design Aspects of Fully Integrated Multiband Multistandard Front-End Receivers	"D:
		Adiseno, , Jan 2003 In this thesis, design aspects of fully integrated multibandmultistandard front-end receivers are investigated based onthree fundamental aspects: noise, linearity and operatingfrequency. System level studies were carried out to investigate the effects of Full text available from DiVA (KTH) similar results	Re us for
	2.	Design Aspects of Fully Integrated Multiband Multistandard Front-End Receivers  Adiseno, , Aug 2003architectures that eliminate the external IF-filtering and possibly external VCO resonatorsfacilitating monolithic integration. However, DC offset, phase and gain imbalance, and flickerbe filtered by using normal monolithic filtering techniques such as gm-C continuos-time  Full text thesis available via NDLTD (DiVA at Uppsala University)	noi sig tra Or Al
	_	similar results	F
	3.	Post-fft scaling to reduce multiple effects  Wang, Yi-Hsiu / Gilbert, Jeffrey M., UNITED STATES PATENT AND TRADEMARK  OFFICE PRE-GRANT PUBLICATION, Aug 2003 patno:US20030152021FFT (IFFT), autocorrelation, subcarrier, delay, and so forth. Variousin accordance with the IEEE 802.11a standard. Consequently, eachthat deviate from the IEEE	
		<b>802.11a</b> standard. [0034]FIG. 3 illustratespacket structure that the IEEE <b>802.11a</b> standard requires for informationsymbol timing adjustment. Since <b>OFDM</b> is extremely sensitive to the	
	•	Full text available at patent office. For more in-depth searching go to view all 5 results from Patent Offices similar results	
	4.	Efficient methods for filtering to avoid inter-symbol interference and processing digital signals having large frequency guard bands  Baas, Bevan M. / Gilbert, Jeffrey M. / McFarland, William J. / Meng, Teresa H. / Tehrani, Ardavan Maleki, UNITED STATES PATENT AND TRADEMARK OFFICE PRE-GRANT PUBLICATION. Mar 2003	

patno: US20030058975

...timing diagram of a circular filtering technique which is optimized...in the optimized circular filtering methodology. The input of...in the receive path of an OFDM receiver employing one or...Filter (FIR) 1032. Low-pass filtering is required to greatly attenuate...corrections to the signal, such as DC offset removal and frequency correction...

Full text available at patent office. For more in-depth searching go to CarisNexis\* view all 5 results from Patent Offices similar results

**5.** Fine frequency offset estimation and calculation and use to improve communication system performance

Gilbert, Jeffrey M. / Meng, Teresa H. / Thomson, John / Wang, Yi-Hsu, UNITED STATES PATENT AND TRADEMARK OFFICE PRE-GRANT PUBLICATION, Mar 2003 patno: US20030058966

...FFT (IFFT), autocorrelation, subcarrier, delay, and so forth. Various...in accordance with the IEEE 802.11a standard. Consequently, each...that deviate from the IEEE 802.11a standard. [0035]FIG. 3 illustrates...packet structure that the IEEE 802.11a standard requires for information...symbol timing adjustment. Since OFDM is extremely sensitive to the...

Full text available at patent office. For more in-depth searching go to LexisNexisview all 5 results from Patent Offices similar results

6. POST-FFT SCALING TO REDUCE MULTIPLE EFFECTS AND FINE FREQUENCY OFFSET **ESTIMATION** 

GILBERT, Jeffrey M. / MENG, Teresa H. / THOMSON, John / WANG, Yi-Hsiu (ATHEROS COMMUNICATIONS, INC.), PATENT COOPERATION TREATY APPLICATION, Apr 2003

patno: WO03028270

...of multiple modulated subcarriers in an t OFDM system, I Figure lb...spectrum t of multiple subcarriers;. Figure 2 illustrates...structure that the IEEE 802.1 la standard requires...spectrum of received 802.11 a OFDM symbols, including carrier...leak, and a receiver's **DC offset**; FigureIO illustrates...

Full text available at patent office. For more in-depth searching go to CLEXISNEXIS\* view all 5 results from Patent Offices similar results

7. MODEM FOR WIRELESS LOCAL AREA NETWORK

SORRELLS, David F. / BULTMAN, Michael J. / COOK, Robert W. / LOOKE, Richard C. / MOSES, Charley, D., Jr. / RAWLINS, Gregory S. / RAWLINS, Michael W. (Parkervision, Inc.), EUROPEAN PATENT, May 2002 patno: EP1206831

...frequency up-conversion, and filtering. Also, schemes exist for...chrominance signal onto a subcarrier. The document US 5809060...re-radiation that is caused by DC offset. The WLAN transmitter includes...unified down-conversion and filtering (UDF) module; FIG. 14 illustrates...6) (MAC Interface) (5.0) (802.11) (Physical Layer Configurations...unified down-conversion and filtering, and combinations and applications...

Full text available at patent office. For more in-depth searching go to \*LexisNexis\* view all 5 results from Patent Offices similar results

:::fast

"DC offset" AND ofdm AND "802.11a" AND filtering AN

Search

"DC offset" AND ofdm AND "802.11a" AND filtering AND subcarrier results on scirus.... Page 3 of 3

☑ Journal sources ☑ Preferred Web sources ☑ Other Web sources ☐ Exact phrase

<u>Downloads</u> | <u>Library Partners</u> | <u>Subscribe to News Updates</u> | <u>User Feedback</u> <u>Advertising</u> | <u>Tell A Friend</u> | <u>Terms Of Service</u> | <u>Privacy Policy</u> | <u>Legal</u>

Powered by FAST © Elsevier 2007

#### MODEM FOR WIRELESS LOCAL AREA NETWORK

Publication number: EP1206831

**Publication date:** 

2002-05-22

Inventor:

SORRELLS DAVID F (US); BULTMAN MICHAEL J (US); COOK ROBERT W (US); LOOKE RICHARD C (US); MOSES CHARLEY D JR (US); RAWLINS GREGORY S (US); RAWLINS MICHAEL W (US)

**Applicant:** 

PARKERVISION INC (US)

Classification:

international:

H03C3/40: H03D3/00: H03D7/00: H03C3/00: H03D3/00:

H03D7/00; (IPC1-7): H03C3/40

- European:

H03C3/40; H03D3/00B Application number: EP20000952520 20000804

Priority number(s): WO2000US21359 20000804; US19990147129P

19990804; US20000525615 20000314; US20000526041

20000314

Also published as:




WO0111767 (A1) EP1206831 (A0) EP1206831 (B1) DE60014930T (T2)

Report a data error here

Abstract not available for EP1206831 Abstract of corresponding document: WO0111767

A transmitter (7102) includes a balanced modulator/up-converter (7104), a control signal generator (7142), an optional filter (7106) and an optional amplifier (7108). Transmitter (7102) upconverts a baseband signal (7110) to produce an output signal (7140) that is conditioned for wireless or wire line transmission. In doing so, the balanced modulator (7104) receives the baseband signal (7110) and samples the baseband signal in a differential and balanced fashion according to the first and second control signals that are phase shifted with respect to each other and so generated a harmonically rich signal (7138). The resulting harmonically rich signal (7138) includes multiple harmonic images that repeat at harmonics of the sampling frequency information to reconstruct the baseband signal.



Data supplied from the esp@cenet database - Worldwide



Home | Login | Logout | Access Information | Alerts | Purchase History | Cart |

#### Welcome United States Patent and Trademark Office

**Search Results** 

**BROWSE** 

Check to search only within this results set

**SEARCH** 

**IEEE XPLORE GUIDE** 

Results for "((dc offset and ofdm and 802.11a and filtering and subcarrier)<in>metadata)"

Your search matched 0 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» Search Options

View Session History

**New Search** 

**Modify Search** 

((dc offset and ofdm and 802.11a and filtering and subcarrier)<in>metadata)

© Citation C Citation & Abstract

Search

⊠e-mail

» Key

IEEE Journal or

**IEEE JNL** 

Magazine

**IET JNL** 

IET Journal or Magazine

**IEEE CNF** 

**IET CNF** 

IEEE Conference Proceeding

**IET Conference** Proceeding

IEEE STD IEEE Standard

Display Format:

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistan

Help Contact Us Privacy &:

© Copyright 2006 IEEE -

Indexed by



Home | Login | Logout | Access Information | Alerts | Purchase History | Cart |

#### **Welcome United States Patent and Trademark Office**

**Search Results** 

**BROWSE** 

SEARCH

IEEE XPLORE GUIDE

Results for "((dc offset and ofdm and filtering and subcarrier)<in>metadata)"

Your search matched 1 of 1643271 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

#### » Search Options

View Session History

**New Search** 

Modify Search

Display Format:

((dc offset and ofdm and filtering and subcarrier)<in>metadata)

Search

☑ e-mail

» Key

IEEE JNL IEEE Journal or

Magazine

IET JNL

**IET CNF** 

IET Journal or Magazine

IEEE CNF IEEE Conference

Proceeding

IET Conference

Proceeding

IEEE STD IEEE Standard

view selected items | Select All Deselect All

Check to search only within this results set

1. Low-cost MIMO real-time demonstrator: concept and first results

Citation C Citation & Abstract

Kuropatwinski, W.; Lillie, F.; Geng, N.; Jondral, F.K.;

Smart Antennas, 2004. ITG Workshop on

2004 Page(s):25 - 29

Digital Object Identifier 10.1109/WSA.2004.1407643

AbstractPlus | Full Text: PDF(923 KB) | IEEE CNF

Rights and Permissions

Help Contact Us Privacy &:

© Copyright 2006 IEEE -

Indexed by inspect



Home | Login | Logout | Access Information | Alerts | Purchase History |

#### Welcome United States Patent and Trademark Office

⊡Search Re	sults		BROWSE	SEARCH	IEEE XPLORE O	SUIDE
Your searc	"((dc offset and ofdm and h matched 2 of 1643271 do n of 100 results are displaye	cuments.	· -	in <b>Descending</b> ord	er	<b>⊠</b> e-mail
» Search O	ptions		•			
View Sessi	on History	Mod	dify Search			
New Searc	<u>h</u>	((dc	offset and ofdm and filtering) <in< td=""><td>&gt;metadata)</td><td></td><td>Search</td></in<>	>metadata)		Search
			Check to search only within t	his results set		
» Key		Disp	play Format:   © Citation	Citation & Ab	stract	
IEEE JNL	IEEE Journal or Magazine	,				
IET JNL	IET Journal or Magazine	t-{ ∧ie	ew selected items   Selec	t All Deselect All		
IEEE CNF	IEEE Conference Proceeding IET Conference Proceeding		1. A Low-Power Dual-Ba Maeda, T.; Matsuno, N Walkington, R.; Numata Solid-State Circuits, IEI	.; Hori, S.; Yamase, a, K.; Yoshida, N.; T	T.; Tokairin, T.; Yanaş	gisawa, K.; Ya
IEEE STD	IEEE Standard		Volume 41, Issue 11, Digital Object Identifier	Nov. 2006 Page(s):		
			AbstractPlus   Full Text Rights and Permissions		EEE JNL	
			2. Low-cost MIMO real-ti Kuropatwinski, W.; Lillie Smart Antennas, 2004. 2004 Page(s):25 - 29 Digital Object Identifier AbstractPlus   Full Text Rights and Permissions	e, F.; Geng, N.; Jone ITG Workshop on 10.1109/WSA.2004 :: PDF(923 KB) IE	dral, F.K.; 9.1407643	suits

Indexed by ធ្យា Inspec° Help Contact Us Privacy &:

© Copyright 2006 IEEE -



Home | Login | Logout | Access Information | Alerts | Purchase History | Cart.

#### Welcome United States Patent and Trademark Office

**□□**Search Results

**BROWSE** 

**SEARCH** 

**IEEE XPLORE GUIDE** 

_			
Your searc	"((dc offset and ofdm and h matched 2 of 1643271 do n of 100 results are displaye	,	-mail
» Search O	ptions		•
View Sessi	on History	Modify Search	
New Searc	<u>h</u>	((dc offset and ofdm and filter) <in>metadata)</in>	rch.
		Check to search only within this results set	
» Key		Display Format:	
IEEE JNL	IEEE Journal or Magazine		
IET JNL	IET Journal or Magazine	view selected items   Select All   Deselect All	
IEEE CNF	IEEE Conference Proceeding	1. A Low-Power Dual-Band Triple-Mode WLAN CMOS Transceiver	
IET CNF	IET Conference Proceeding	Maeda, T.; Matsuno, N.; Hori, S.; Yamase, T.; Tokairin, T.; Yanagisawa, K Walkington, R.; Numata, K.; Yoshida, N.; Takahashi, Y.; Hida, H.;	i.; Ya
IEEE STD	IEEE Standard	Solid-State Circuits, IEEE Journal of Volume 41, Issue 11, Nov. 2006 Page(s):2481 - 2490 Digital Object Identifier 10.1109/JSSC.2006.883323	

2. Low-cost MIMO real-time demonstrator: concept and first results Kuropatwinski, W.; Lillie, F.; Geng, N.; Jondral, F.K.;

Smart Antennas, 2004. ITG Workshop on

2004 Page(s):25 - 29

Rights and Permissions

Digital Object Identifier 10.1109/WSA.2004.1407643

AbstractPlus | Full Text: PDF(2008 KB) IEEE JNL

AbstractPlus | Full Text: PDF(923 KB) IEEE CNF

Rights and Permissions

Help Contact Us Privacy &:

© Copyright 2006 IEEE -

Indexed by 面 inspec\*

PALM Intranet	
Application Submit Number	
IDS Flag Clearance for Application 10700474	

Content	Mailroom Date	Entry Number	IDS Review	Last Modified	Reviewer
WIDS	2004-01-30	28	Y	2007-06-12 10:14:04.0	CR #235743
Update					

. PALM INTRANET

Day: Tuesday Date: 9/18/2007

Time: 10:28:47

# **Continuity Information for 10/700474**

Parent Data No Parent Data	
Child Data No Child Data Apple Info Contents Petition Info Atty/Ag	ent Info Continuity/Reexam Foreign Data
Search Another: Application # Search	or Patent# Search
PCT / / Search	or PG PUBS #
Attorney Docket #  Bar Code #	Search

To go back use Back button on your browser toolbar.

PALM INTRANET

Day: Tuesday Date: 9/18/2007

Time: 10:28:54

# Foreign Information for 10/700474

## No Foreign Data

Appln Info Contents Petition Info Atty/Age	ent Info Continuity/Reex	am Foreign Data
Search Another: Application # Search	or Patent#	Search
PCT / Search	or PG PUBS #	
Attorney Docket #	Search	
Bar Code #	Search	

To go back use Back button on your browser toolbar.

Day: Tuesday Date: 9/18/2007

## PALM INTRANET

Time: 10:29:31

## **Inventor Information for 10/700474**

Inventor Name	City	State/Country
HWANG, CHIEN-MEEN	SAN JOSE	CALIFORNIA
KUTAGULLA, HARISH	AUSTIN	TEXAS
ZHOU, XU	SUNNYVALE	CALIFORNIA
Appln Info Contents Petition Info  Search Another: Application #  Search	Atty/Agent Info Cont	inuity/Reexam Foreign
<b>PCT</b> /  /	Search or PG PUB	SS#
Attorney Docket #	Sear	ch

Search

To go back use Back button on your browser toolbar.

Bar Code #

PALM INTRANET

Day: Tuesday Date: 9/18/2007

Time: 10:29:36

## **Inventor Name Search Result**

Your Search was:

Last Name = HWANG

First Name = CHIEN-MEEN

Application#	Patent#	Status	Date Filed	Title	Inventor Name
08468280	5640698			RADIO FREQUENCE SIGNAL RECEPTION USING FREQUENCY SHIFTING BY DISCRETE- TIME SUB- SAMPLING DOWN- CONVERSION	HWANG, CHIEN- MEEN
<u>08499315</u> .	5604464	150	07/07/1995	CASCODE OPERATIONAL AMPLIFIER WITH MULTIPLE INPUT STAGE	HWANG, CHIEN- MEEN
09286987	6339599	150	04/07/1999	COLLISION HANDLING SCHEME FOR DISCRETE MULTI-TONE DATA COMMUNICATIONS NETWORK	HWANG, CHIEN- MEEN
09286989	6434188	150	04/07/1999	DIFFERENTIAL ENCODING ARRANGEMENT FOR A DISCRETE MULTI-TONE TRANSMISSION SYSTEM	HWANG, CHIEN- MEEN
09286991	6252428	150	04/07/1999	METHOD AND APPARATUS FOR DETECTING A SINUSOIDAL SIGNAL	HWANG, CHIEN- MEEN
09286992	6456602	150	04/07/1999	METHOD AND APPARATUS FOR ACHIEVING FREQUENCY DIVERSITY BY USE OF MULTIPLE IMAGES	HWANG, CHIEN- MEEN
09286993	6449262	150	04/07/1999	METHOD AND APPARATUS FOR FREQUENCY SHIFTING WITH A CLOCK SIGNAL	HWANG, CHIEN- MEEN
09286994	6075795	150	04/07/1999	COLLISION DETECTION SYSTEM FOR MULTIPLE STATIONS IN DISCRETE MULTI-TONE DATA COMMUNICATIONS NETWORK	HWANG, CHIEN- MEEN

09286995	6442173	150			HWANG, CHIEN- MEEN
09286996	6577598	150		FOR CHANNEL ADAPTATION IN A DMT BASED SYSTEM	HWANG, CHIEN- MEEN
09286997	6590893	150		SYSTEM IN A NETWORK	HWANG, CHIEN- MEEN
09286998	6246267	150		METHOD AND APPARATUS FOR DETECTING A SINUSOIDAL SIGNAL USING A COUNTER AND QUEUE	HWANG, CHIEN- MEEN
09287263	6175316	150	04/07/1999	BIN-TO-BIN DIFFERENTIAL ENCODING APPARATUS AND METHOD FOR A DISCRETE MULTI-TONE TRANSMISSION SYSTEM	HWANG, CHIEN- MEEN
09357724	6498807	150	07/21/1999	METHOD AND APPARATUS FOR TRANSMITTING DATA FROM A PLURALITY OF USERS IN A MULTI-TONE MODEM COMMUNICATIONS SYSTEM	HWANG, CHIEN- MEEN
09359343	6501791	150	07/21/1999	METHOD AND APPARATUS FOR ALLOCATING TONES TO A PLURALITY OF USERS IN A MULTI-TONE MODEM COMMUNICATIONS SYSTEM	HWANG, CHIEN- MEEN
09378831	Not Issued	163	08/23/1999	METHOD AND APPARATUS FOR OPTIMAL DATA TRANSFER IN A MULTI-TONE MODEM COMMUNICATIONS SYSTEM	HWANG, CHIEN- MEEN
09497030	6728325	150	02/02/2000	METHOD AND APPARATUS FOR MIXING DOWN AND SPECTRUM FOLDING FREQUENCY DIVERSE MODULATED CARRIER	HWANG, CHIEN- MEEN
09510775	6651078	150	02/23/2000	METHOD FOR DETERMINING A DECIMATION PATTERN IN A NETWORK COMMUNICATIONS RECEIVER	
09536528	6661849	150	03/28/2000	MULTIPLE PAYLOAD SLICER SYSTEM WITH PRENORMALIZATION INTEGER VALUES	HWANG, CHIEN- MEEN

. ·					
09755857	Not Issued	161		Network receiver utilizing sample management buffers with slower sampling rates during training sequence	HWANG, CHIEN- MEEN
09897198	6441683	150		DEVICE AND METHOD FOR RECOVERING FREQUENCY REDUNDANT DATA IN A NETWORK COMMUNICATIONS RECEIVER	HWANG, CHIEN- MEEN
10367777	7233612	150	02/19/2003	WIRELESS COMMUNICATION DEINTERLEAVER USING MULTI-PHASE LOGIC AND CASCADED DEINTERLEAVING	HWANG, CHIEN- MEEN
10367864	Not Issued	71		Wireless receiver deinterleaver having partitioned memory	HWANG, CHIEN- MEEN
10367865	7251273	150	02/19/2003	MINIMUM EQUALIZATION ERROR BASED CHANNEL ESTIMATOR	HWANG, CHIEN- MEEN
10458285	7248637	150	06/11/2003	VITERBI DECODER UTILIZING PARTIAL BACKTRACING	HWANG, CHIEN- MEEN
10612954	Not Issued	123	07/07/2003	Optimal initial gain selection for wireless receiver	HWANG, CHIEN- MEEN
10633033	Not Issued	41	08/04/2003	Time domain estimation of IQ imbalance in a wireless OFDM direct conversion receiver	HWANG, CHIEN- MEEN
10699667	7184714	150	11/04/2003	FREQUENCY DOMAIN ESTIMATION OF IQ IMBALANCE IN A WIRELESS OFDM DIRECT CONVERSION RECEIVER USING LOOPBACK CONNECTION	HWANG, CHIEN- MEEN
10700474	Not Issued	41	11/05/2003	DC offset cancellation in a direct conversion receiver configured for receiving an OFDM signal	HWANG, CHIEN- MEEN
10768073	7274758	150	02/02/2004	COARSE FREQUENCY ESTIMATION IN AN OFDM RECEIVER BASED ON AUTOCORRELATION OF ACCUMULATED SAMPLES	HWANG, CHIEN- MEEN
10790205	Not Issued	41		Fast fourier transform circuit having partitioned memory for minimal latency during in-place computation	HWANG, CHIEN- MEEN
10816876	7274757	150	04/05/2004	AUTOCORRELATION	HWANG, CHIEN-

				THRESHOLD GENERATION BASED ON MEDIAN FILTERING FOR SYMBOL BOUNDARY DETECTION IN AN OFDM RECEIVER	MEEN
10839351	Not Issued	30			HWANG, CHIEN- MEEN
60225560	Not Issued	159		Device and method for recovering frequency redundant data in a network communications receiver	HWANG, CHIEN- MEEN
60957199	Not Issued	20	08/22/2007	High Resolution Variable Gain Control	HWANG, CHIEN- MEEN
60969430	Not Issued	-20	08/31/2007	VARIABLE GAIN AMPLIFIER	HWANG, CHIEN- MEEN

Inventor Search Completed: No Records to Display.

	Last Name	First Name	
Search Another: Inventor	HWANG	CHIEN-MEEN	Search

To go back use Back button on your browser toolbar.

PALM INTRANET

Day: Tuesday Date: 9/18/2007

Time: 10:29:45

### **Inventor Name Search Result**

Your Search was:

Last Name = KUTAGULLA

First Name = HARISH

Application#	Patent#	Status	Date Filed	Title	Inventor Name
10633033	Not Issued		08/04/2003	Time domain estimation of IQ	KUTAGULLA, HARISH
10699667	7184714	150	11/04/2003		KUTAGULLA, HARISH
10700474	Not Issued	41	11/05/2003	DC offset cancellation in a direct conversion receiver configured for receiving an OFDM signal	KUTAGULLA, HARISH
10817811	Not Issued	41	04/06/2004	OFDM receiver having adaptive channel estimator for correcting channel fading based on accumulated pseudo power values	KUTAGULLA, HARISH
11054220	Not Issued	30	02/09/2005	Data processor adapted for efficient digital signal processing and method therefor	KUTAGULLA, HARISH
11086881	Not Issued	41	03/22/2005	Data generation and collection from a real-time system for non-real-time software simulation	KUTAGULLA, HARISH

Inventor Search Completed: No Records to Display.

Search Another: Inventor Last Name First Name

KUTAGULLA HARISH Search

To go back use Back button on your browser toolbar.

PALM INTRANET

Day: Tuesday Date: 9/18/2007

Time: 10:30:04

# **Correspondence Address for 10/700474**

Customer Number	Contact Information	Address			
20736 Delivery Mode: <u>PAPER</u>	Telephone: (202)261-1000 Fax: (202)887-0336 E-Mail: No E-Mail Address	MANELLI DENISON & SELTER 2000 M STREET NW SUITE 700 WASHINGTON DC 20036-3307			
Appln Info Contents	Petition Info Atty/Agent Info	Continuity/Reexam Foreign			
Search Another: Ap	oplication #	or Patent# Search			
PCT /	/ Search	or PG PUBS # Search			
Attorney	y Docket #	Search			
Bar Cod	Bar Code # Search				

To go back use Back button on your browser toolbar.